



TL-530 Toploader

The TL-530 is with 4 profiles is the starter of the Eurotruss lifters family. The TL-530 can lift loads up to 150 kg to a maximum of 5.3 meters high. The high resistance cable for traction is guided by an auto-lubricated pulley.

The lifter is fixed with hyper safety fastener locks to bear lifter strain. Adjustable stabilizers on its legs provide stability in all kind of surface whereas a bubble level allow to balance it.

Four wheels ensure an easy use and transport.
All Eurotruss lifters are powdercoated black.

Facts

- Unique locking bolts to bear lifter strain
- Four steel profiles
- Automatic brake winches (manufactured to the VGB 8/10.93 standard.
- Auto-lubricated pulley & high resistance cable
- 35 mm top is suitable with many accessories.
- Additional center stabilizer for better load distributing

Specifications TL-530 Toploader

Weight of the lifter:	43.4 kg.	Diameter of toppart:	35 mm.
Min load:	25 kg.	Unfolded base:	1.49 x 1.49 m.
Max load:	150 kg.	Folded base:	0.36 x 0.36 m.
Min height:	1.72 m.	Number of profiles:	4
Max height:	5.30 m.		

* For imperial info - See page 249



Pulley system and safety pin on each section. Vertex with reinforcement.



High resistance stabilizer legs are equiped with rubber feet base.



The TL-530 is a 4 wheel base lifter. During transport stabilizer legs can be put in the space provided in the base.