

Ovation™ C-640FC



Ovation™ C-640FC is a great replacement to for widely used halogen cyc lights. It can create any color in the gel books while consuming less power than traditional-style fixtures. It's theatre-ready with 16-bit dimming control (of each color) as well as a master dimmer and a virtual color wheel.

FEATURES

- Display a full spectrum of hues with RGBWA LEDs for versatility
- Static color mixing without DMX control
- Theatre-ready with 16-bit dimming of master dimmer and individual colors
- Better coverage with two individually adjustable heads
- Compact cyclorama wash lighting fixture

SPECIFICATIONS

- DMX Channels: 3, 4, 5, 6, 7, 8, 12, 18 or 24
- Data Connectors: 3- and 5-pin XLR
- Light Source: 64 LEDs (16 red, 16 green, 16 blue, 8 white, 8 amber) 3 to 5 W, (850 mA), 50,000 hours life expectancy
- Built-in Automated Programs: Yes
- Customizable Programs: Yes
- Recall Custom Programs: Yes
- Accessory Holder/
Gel Frame Size: 5.32 x 9.65 in (135 x 245 mm)
- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 20 Hz
- Stand Alone Color Mixing: Yes
- Color Temperature Presets: Yes
- Beam Angle: 35°
- Field Angle: 65°
- Dimming Modes: 5
- Illuminance: 141 lux @ 5 m
- Color Temperature (range): 2800 to 10000 K
- IP Rating: IP20, dry location
- Cable Length: 5 ft (1.5 m)
- Power Connection: Edison plug to Neutrik® powerCON®
- Power Input: Neutrik® powerCON®
- Power Output: Neutrik® powerCON®
- Power Linking: 9 units @ 120 V; 16 units @ 208 V; 18 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 175 W, 1.44 A @ 120 V, 60 Hz
- Power and Current: 173 W, 0.83 A @ 208 V, 60 Hz
- Power and Current: 173 W, 0.76 A @ 230 V, 50 Hz
- Weight: 22 lb (9.98 kg)
- Dimensions: 15.3 x 12.2 x 11.7 in (390 x 310 x 298 mm)
- Approvals: CE, MET